





















Rod Seals						
Profile	Type	Standard Material	Pressure (bar) <sup>1</sup>	Temperature (°C) <sup>1</sup>	Sliding Speed (m/sec) <sup>1</sup>	Description
	T1	NBR-Fabric FKM	250	-30 to 110 -30 to 140	0,5	Rod seal compact design
	T2	NBR-Fabric Polyacetal FKM / PGM	500	-30 to 110 -30 to 140	0,5	Rod seal compact design with support ring
	T3	NBR-Fabric FKM	250	-30 to 110 -30 to 140	0,5	Rod seal, compact design with groove ring
	T4 SGA	NBR Polyesterelastomer	700	-30 to 100	0,5	Rod seal, 2-piece with support ring
	VP5	NBR-Fabric/NBR FKM-Fabric/FKM	400	-30 to 110 -30 to 140	0,5	Rod seal, 5-piece chevron-type seal
	VP6	NBR-Fabric/NBR FKM-Fabric/FKM	400	-30 to 110 -30 to 140	0,5	Rod seal, 6-piece chevron-type seal
	VP7	NBR-Fabric/NBR FKM-Fabric/FKM	400	-30 to 110 -30 to 140	0,5	Rod seal, 7-piece chevron-type seal
	T7 S	Polyurethane	400	-40 to 100	0,5	Rod seal, compact groove ring
	T7/L SD	Polyurethane	400	-40 to 100	0,5	Rod seal, compact groove ring with secondary lip
	T7/L S DA	Polyurethane Polyacetal	450	-40 to 100	0,5	Rod seal, compact groove ring with secondary lip and support ring
	T10 A10	Polyurethane	400	-40 to 100	0,5	Groove ring with asymmetric lip shape
	T10/L A10/L	Polyurethane	400	-40 to 100	0,5	Groove ring with asymmetric lip shape and support ring
	T10/L S ADA	Polyurethane Polyacetal	450	-40 to 100	0,5	Groove ring with asymmetric lip shape, support ring and sec. lip
	T10/S	Polyurethane Polyacetal	450	-40 to 100	0,5	Groove ring with asymmetric lip shape and support ring
	T11 UP	Polyurethane	400	-40 to 100	0,5	Groove ring with symmetric lip shape
	SDAN	Polyurethane O-ring NBR Polyacetal	500	-40 to 100	0,5	Groove ring with asymmetric lip shape, support ring and O-ring
	UPN	Polyurethane O-ring NBR	400	-40 to 100	0,5	Groove ring with symmetric lip shape and O-ring
	T12	Polyurethane Polyacetal	450	-40 to 100	0,5	Groove ring, compact design with support ring
	NCR	PTFE-compound O-ring NBR / FKM	800	-30 to 110 -30 to 200	15	single-acting Rod seal, 2-piece
	NCS	PTFE-compound O-ring NBR / FKM	800	-30 to 110 -30 to 200	15	double-acting Rod Seal 2-piece