













Symmetric Seals

Profile	Type	Standard Material	Pressure (bar) ²	Temperature (°C) ²	Sliding Speed (m/sec) ²
	PRS06	PU NBR	400 160	-30 to 105 -25 to 100	0,5
	PRS06A	PU NBR	400 160	-30 to 105 -25 to 100	0,5
	PRS06B	PU NBR	400 160	-30 to 105 -25 to 100	0,5
	PRS06C	PU NBR	400 160	-30 to 105 -25 to 100	0,5
	PRS06E	PU NBR	400 160	-30 to 105 -25 to 100	0,5
	PRS07	PU/NBR	400	-25 to 100	0,5
	PRS13-15	PU/POM NBR/POM FKM/PGM	500 250 250	-30 to 100 -25 to 100 -20 to 210	0,5
	PRS18	PU/NBR	400	-25 to 100	0,5
	PRS19B	PGM/1.4310	150	-200 to 260	2
	PRS19D	PGM/1.4310	150	-200 to 260	2
	PRS22	PU/POM NBR/POM FKM/PGM	400 160 160	-30 to 100 -25 to 100 -20 to 210	0,5
	PRS10-12	PU/POM NBR/POM FKM/PGM	500 250 250	-30 to 100 -25 to 100 -20 to 210	0,5